



COVENCA
ventilación

HONGO CENTRÍFUGO DIRECTO



TABLA DE SELECCIÓN

MODELO	CAPACIDADES																																				
	Barras en BLANCO sistema métrico en MCN								Barras en NARANJA sistema ingles en PCM																												
MODELO R.P.M	0mm	3.2mm	6.4mm	9.5mm	12.7mm	15.9mm	19.1mm	22.3mm	25.4mm	28.6mm	31.8mm	35.0mm	38.1mm	41.3mm	44.5mm	47.7mm																					
	0"	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"	1 1/8"	1 1/4"	1 3/8"	1 1/2"	1 5/8"	1 3/4"	1 7/8"																					
HCDCF-8 1550	21.2	19.5	18.3	18.0	15.8	13.2	12.3	9.2	750	688	646	635	559	465	436	325																					
1200	35.3	32.3	29.1	25.8	23.1	18.4	11.6																														
HCDCF-10	1.248	1.140	1.028	912	816	651	410																														
1800	46.7	44.5	41.5	40.0	38.4	36.4	34.4	32.2	27.6	26.9	24.1	21.5	16.4																								
HCDCF-12 1200	1.650	1.572	1.466	1.411	1.355	1.286	1.215	1.138	976	949	852	760	578																								
900	56.9	53.0	48.5	43.5	38.2	33.9	29.9	25.5	17.7	2.010	1.873	1.714	1.535	1.348	1.197	1.057	899	625																			
HCDCF-15	64.5	57.7	50.4	44.3	39.1	32.8	28.0	2.276	2.039	1.778	1.563	1.379	1.158	988																							
1200	87.8	80.1	74.3	68.4	63.1	57.1	53.4	49.2	44.2	39.4	35.3	24.5	12.7	3.100	2.827	2.623	2.415	2.228	2.015	1.886	1.739	1.562	1.391	1.246	865	450											
900	94.6	89.1	75.1	65.8	59.3	51.8	45.9	36.6	27.1	8.5	3.340	3.145	2.653	2.324	2.095	1.828	1.621	1.294	958	300																	
HCDCF-18	134.5	121.8	111.9	105.8	96.4	87.4	79.6	73.8	70.5	65.1	57.9	50.3	42.3	27.3	14.9	4.750	4.300	3.951	3.735	3.404	3.085	2.812	2.607	2.488	2.300	2.046	1.777	1.492	965	525							
1200	121.8	117.5	109.3	103.7	99.1	93.2	86.7	82.8	79.3	74.6	72.1	70.8	59.5	51.7	43.8	35.4																					
HCDCF-20 1200	4.300	4.150	3.860	3.660	3.500	3.290	3.060	2.925	2.800	2.635	2.545	2.500	2.100	1.825	1.545	1.250																					

TAMAÑO	MOTOR				A	B	C	D	E	F	G	H*	
	R.P.M.*	H.P.	V**	F									
HCDCF-8	1.550	1/10	115	1	20 7/8	18 1/4	7 3/32	20	1 1/2		498	300	400
					530	464	180	508	38				
HCDCF-10	1.200	1/6	115	1	20 7/8	21 1/8	7 7/8	20	1 1/2		498	300	400
	1.200	0.5	220/440	3									
	1.800	1/3	115	1	530	537	200	508	38				
	1.800	0.5	220/440	3									
HCDCF-12	1.200	1/3	115	1	27 9/16	24 1/4	10 1/8	21	1 1/2		524	410	400
	1.200	0.5	220/440	3	700	616	257	533	38				
HCDCF-15	900	0.5	220/440	3	32	27 1/4	14	26	2		650	460	450
	1.200	1.0	220/440	3	813	692	356	660	50				
HCDCF-18	900	1.0	220/440	3	39 1/2	30 7/8	14	35	2		880	670	500
	1.200	1.5	220/440	3	1.003	784	356	889	50				
HCDCF-20	1.200	2.0	220/440	3	39 1/2	30 7/8	14	35	2		880	670	500
					1.003	784	356	889	50				